

TS101-40 40 Watt Radio Transceiver

The TS101-40 is a 40 watt digital FM radio transceiver that is specifically designed for voice and data paging applications. The unit contains a synthesized UHF or VHF transmitter with a highly sensitive receiver for channel monitoring. The TS101-40 comes with an integrated switching power supply to support the transceiver's stable operation.



- *UHF or VHF Frequency Band*
- *Digital and Analog Paging Formats*
- *40 Watt Power Output*
- *Synthesized Frequency*
- *Highly Sensitive Receiver*
- *Narrow Band Operation*

Specifications:

Dimensions:	3.5" H x 14" W x 11.5" D	Frequency Range:	148-174Mhz, 400-470MHz
Weight:	8.55 lb.	Channel Spacing:	12.5 KHz - Narrow band
Power input:	90-240VAC 50/60Hz 120Watt	Stability:	± 2.5 ppm
Operating Temperature:	10° to 140°F	Data format:	Digital 512-2400 BPS Analog - 100Hz - 3.6KHz
Output Power:	Up to 40 Watt	Enclosure:	Durable metal case with LED power , PTT and data indicators.
Receiver Sensitivity:	<110dBm	Limited Warranty:	One-year Parts and Labor
Selectivity:	50dB		
Input/Output impedance:	50 Ohm		

Preferred Communications
410 Central Avenue
Butner, NC 27509

Phone: 1-800-300-6020
Fax: 1-919-575-4600



Preferred Communications

www.satstar.com